

MICROCOVE AC Indirect



Indirect | Standard Lengths

Project Name _____

Fixture Type _____



Integral Driver

DESCRIPTION

1.4" Low-Profile Linear LED Cove Mount

The MICROCOVE AC Indirect (ACI) is part of the innovative family of ultra-slim and compact LED linear products providing best-in-class efficiency and beam control options. The MICROCOVE ACI is designed to fit into the smallest of cove spaces and is specification-grade with high lumen per foot, high CRI, and circadian options. MICROCOVE ACI uses engineered light engines with fully customizable choices for lumen output, CCT, and CRI. Designed to be surface mounted. MICROCOVE ACI can also be daisy-chained with individual fixtures placed end-on-end in a tight packed formation to create long continuous runs of light.

Features & Benefits

Small Form Factor with Exceptional Performance
 1.4" x 1.4" delivering up to 1,250 lm/ft, 150 lm/W efficacy

Wide Range of LED Selections

Static, Tunable White, and Dim-to-Warm. 90/95+ CRI, 2700K to 6500K CCT.

AC Power Input with Dimming & Control Options

Direct AC input (110V-277V) wide range of control options including 0-10V, DALI, DMX, and TRIAC dimming

Patented Innovations

Fusion Optix® Inside with unique SmartBeam® capabilities

Proprietary Optical Components

Provides excellent light distribution and high-transmission

Committed to Made-in-USA & Sustainability

Designed & built in Boston MA, Declare Listed and Red Free List materials

Compliance


UL Listed, Dry and Damp Locations

5-Year Warranty

Standard 5-year warranty, 50,000 hours

LIGHTING CONFIGURATIONS

Indirect



Designed & Built in
BOSTON

FIXTURE ORDERING

Project Name _____

Fixture Type _____

1) FIXTURE DESIGN

PRODUCT	FIXTURE LENGTH	MOUNTING TYPE	FINISH	POWER EXTENSION CORD	DAISY CHAIN
MCV-ACI 1.4" Low-Profile Linear LED Cove Mount with AC Power for Indirect Lighting	1 - 1 ft 2 - 2 ft 3 - 3 ft 4 - 4 ft 6 - 6 ft 8 - 8 ft X_ - Specify Ft', In" 1 ft / 12.2" available only in static white	SFM - Surface Fixed Mount	Powder Coated PMW - Matte White	EC6W - 6" White Extension Cable EC12W - 12" White Extension Cable EC24W - 24" White Extension Cable EC48W - 48" White Extension Cable	DN - No: Daisy Chain DY - Yes: Daisy Chain

2) LED LIGHT ENGINE

CRI	CCT	INDIRECT BEAM PATTERN	INDIRECT OUTPUT
90 - Std. 90 CRI 95 - High-Def. 95 CRI SUN - Full SunLike	27 - 2700K 30 - 3000K 35 - 3500K 40 - 4000K XD - Dim-to-Warm XT - Tunable X_ - Specify CCT Specify Dim-to-Warm and Tunable between 2700K-6500K.	ILAM - Lambertian IBW120 - Batwing120° IFT150 - FlatTop 150° IA6040 - Asym 60° at 40° Tilt X_ - Specify Beam¹	35 - 350 lm/ft 50 - 500 lm/ft 75 - 750 lm/ft 100 - 1,000 lm/ft X_ - Specify lm/ft

3) FIXTURE POWER & CONTROLS



LINE VOLTAGE (DC)	INTEGRAL DRIVER (POWER)
UNV - 120/277V 347 - 347V	FDND - Factory Non-Dimming FD00 - Factory 0-10V 0.1% Dim FD01 - Factory 0-10V 1% Dim FD10 - Factory 0-10V 10% Dim FDDA - Factory DALI 0.1% Dim FDDX - Factory DMX Dim FDTR - Factory TRIAC Dim LD01 - Lutron Hi-Lume 1% Dim X_ - Specify Driver

OPTIONAL

EMERGENCY BACKUP	WIRELESS MODULE
EMC - Emergency Circuit EMB - Emergency Battery (10 W — Remote) X_ - Specify Backup Specify requirements at time of order.	WCN - Wireless Communication Node (Connected to LED Driver In-Fixture or In-Driver Box) PIR - Wireless Communication Node + PIR Sensor (Standard Lens for Low Bay < 10') MW - Wireless Communication Node + MW Sensor (Standard for Low Bay < 10') X_ - Other - Specify Embedded Component or Specific Non-Standard Sensor Detection Range

DIMENSIONS & INSTALLATION

Dimensions



Standard Fixtures

1ft	11.05" / 11.4"
2ft	23.05" / 23.4"
3ft	35.05" / 35.4"
4ft	47.05" / 47.4"
6ft	71.05" / 71.4"
8ft	95.05" / 95.4"

Mounting Type

Cove Mount

Installs into a cove. Available with a range of accessories, mounts and inserts that provide easy customization of visual appearance and performance enhancements

Power Extension Cord


Sizes and Color

6", 12", 24", and 48", White Extension Cords

Connector (AC)

Connector Options

Easy Plug-and-Play Factory Installed Connectors



Factory Connectors

SMARTBEAM® TECHNOLOGY

The Ultimate Control of Lighting Distributions

SmartBeam makes it easy to specify the exact light required for any architectural space. Available in every XICO product; it is now possible to create truly tailored and engaging lighting that transform spaces, improves visual comfort, and saves energy.

To learn more about our SmartBeam Technology, please click or scan the QR Code.



LPW Efficacy Conversion Chart

CODE	CCT SELECTED							
	2200K	2700K	3000K	3500K	4000K	5000K	5700K	6500K
90	-	0.91	0.96	1.00	1.04	1.11	1.11	1.11
95	-	0.91	0.96	1.00	1.04	1.11	1.03	1.04
SUN	-	0.90	0.92	1.00	1.01	1.07	1.04	1.05

LPW Performance

	INDIRECT			
	ILAM	IBW120	IFT150	IA6040
LM/W	150	156	143	143


$$LM/W = \frac{\left(\begin{matrix} \text{DIRECT} \\ \text{LM/FT} \end{matrix} + \begin{matrix} \text{INDIRECT} \\ \text{LM/FT} \end{matrix} \right)}{\left(\begin{matrix} \text{DIRECT} \\ \text{W/FT} \end{matrix} + \begin{matrix} \text{INDIRECT} \\ \text{W/FT} \end{matrix} \right)}$$

INDIRECT PHOTOMETRICS

48" Length, 80+/3500K CRI/CCT, 4,000 Lumens


Static White Light

ILAM: Lambertian




LM/FT	W/FT	LM/W
350	2.3	152.2
500	3.4	147.1
750	5.0	150
1,000	6.7	150

IBW120: Batwing 120°




LM/FT	W/FT	LM/W
350	2.2	
500	3.2	
750	4.8	
1,000	6.4	156

IFT150: FlatTop 150°



LM/FT	W/FT	LM/W
350	2.5	143
500	3.5	142.9
750	5.3	141.5
1,000	7	143


IA6040: Asymmetric 60° at 40° Tilt




LM/FT	W/FT	LM/W
350	2.5	143
500	3.5	142.9
750	5.3	141.5
1,000	7	143

LED OPTIONS


90: Standard 90+ CRI



95: High-Definition 95+ CRI



SUN: Full Spectrum "SunLike"



CODE	DESCRIPTION	TYPICAL LED DATA							
		CCT	CRI	CRI R9	TM30 Rf	TM30 Rg	CQS	M/P Ratio	LPW
90	Standard 90 CRI	3500K	91	54.3	89.3	98.9	89.2	0.55	175
95	High Definition 95 CRI	3500K	97.1	95	-	-	-	0.70	163
SUN	Full Spectrum SunLike®	3500K	95	85	-	-	-	-	130

POWER & CONTROLS

Voltage

Fixture Voltage (AC)

120–277 VAC
347 VAC, 50/60 Hz

Power Location

Integral

LED Driver

Factory Selected, 36–39V Constant Current

Drivers

FDND - Factory Non-Dimming
FD00 - Factory 0-10V 0.1% Dim
FD01 - Factory 0-10V 1% Dim
FD10 - Factory 0-10V 10% Dim
FDDA - Factory DALI 0.1% Dim
FDDX - Factory DMX Dim
FDTR - Factory TRIAC Dim
LD01 - Lutron Hi-Lume 1% Dim
X_ - Specify Driver

Emergency Backup (Optional)

EMC - Emergency Circuit
EMB - Emergency Battery
(10 W — Remote)
X_ - Specify Backup

Power

10 W

Illumination Time

90 minutes

IP Rating

Suitable for Dry and Damp Locations,
indoor use only

XBox

Remote Driver Boxes (Optional)

To create a clean and organized power solution for multiple fixture installations see our Xbox Specification Guide. Reach out to a XICO Sales Representative to discuss your projects needs.

Compatible Control Options



