

# EDGESlim375 Wall

Direct, Indirect, Direct / Indirect | Standard Lengths



Project Name \_\_\_\_\_

Fixture Type \_\_\_\_\_



**Remote Driver**

## DESCRIPTION

### 0.5" x 3.75" Low-Profile Wall Mounted Fixture

The EDGESlim375 Wall from XICO is an innovative ultra-slim and compact wall-mounted LED linear product providing best-in-class efficiency and beam control options. The EDGESlim375 is designed to be specification-grade with high lumen per foot, high CRI, and circadian options. EDGESlim375 does not rely on low-cost LED tape but rather engineered light engines with fully customizable choices for lumen output, CCT, and CRI.

## FEATURES & BENEFITS

### Exceptional Performance

3.75" x 0.5" fixture delivering up to 1,000 lm/ft, 150 lm/W efficacy

### Wide Range of LED Selections

Static, Tunable White, and Dim-to-Warm

### Designed with Options

Wide choice of SmartOptic® lenses, beam distributions, 80/90/95+ CRI, 2700K to 6500K CCT, and 0-10V, DALI, DMX, and TRIAC dimming

### Patented Innovations

Fusion® Optix Inside with unique SmartBeam® capabilities

### Proprietary Optical Components

Provides excellent light distribution and high-transmission

### Committed to Sustainability

Declare Listed and Red Free List materials

### Compliance

UL Listed, Dry and Damp Locations

### 5-Year Warranty


Standard 5-year warranty, 50,000 hours

## LIGHTING CONFIGURATIONS

Direct

Indirect

Indirect / Direct



Designed & Built in **BOSTON**

## FIXTURE ORDERING

Project Name \_\_\_\_\_

Fixture Type \_\_\_\_\_

1) FIXTURE DESIGN				
PRODUCT	FIXTURE LENGTH	FINISH		
<b>ESM375-W</b> 3.75" Low-Profile Linear LED Light Fixture	1 - 1 ft 2 - 2 ft 4 - 4 ft 6 - 6 ft 8 - 8 ft X_ - Specify Ft', In" (Ask Factory)	<b>Powder Coated</b> <b>PMW</b> - Matte White <b>PMB</b> - Matte Black <b>PMG</b> - Matte Gray <b>PRAL_</b> - Specify RAL #  <b>Anodized</b> <b>ACL</b> - Clear Anodized <b>ACU_</b> - Custom Anodized #		
2) LED LIGHT ENGINE				
CRI	CCT	OPTIC (DIRECT ONLY)	DIRECT BEAM PATTERN	DIRECT OUTPUT
<b>80</b> - Std. 80 CRI <b>90</b> - Std. 90 CRI <b>95</b> - High-Def. 95 CRI <b>SUN</b> - Full SunLike	<b>27</b> - 2700K <b>30</b> - 3000K <b>35</b> - 3500K <b>40</b> - 4000K <b>XD</b> - Dim-to-Warm <b>XT</b> - Tunable <b>X_</b> - Specify CCT  Specify Dim-to-Warm and Tunable between 2700K-6500K.	<b>OFL</b> - Flush Lens	<b>NN</b> - Not Needed <b>DW110</b> - Wide 110° <b>DBW60</b> - Batwing 60° <b>DM50</b> - Medium 50° <b>DA7025</b> - Asym 70° at 25° Tilt <b>DA6005</b> - Asym 60° at 5° Tilt <b>DA6005S</b> - Asym 60° at 5° Tilt w/ glare shield  EDGELIT WAVEGUIDE TECHNOLOGY <b>DW120LG</b> - Wide 120° <b>DA6515LG</b> - Asym 65° at 15° Tilt <b>DA8010LG</b> - Asym 80° at 10° Tilt <b>DA4060LG</b> - Asym 40° at 60° Tilt  <b>X_</b> - Specify Beam <sup>1</sup>	<b>NN</b> - Not Needed <b>35</b> - 350 lm/ft <b>50</b> - 500 lm/ft <b>75</b> - 750 lm/ft <b>100</b> - 1,000 lm/ft <b>X_</b> - Specify lm/ft
INDIRECT BEAM PATTERN	INDIRECT OUTPUT	CIRCUIT		
<b>NN</b> - Not Needed <b>ILAM</b> - Lambertian <b>IBW60</b> - Batwing 60° <b>IM50</b> - Medium 50° <b>IA4560</b> - Asym 45° at 60° Tilt <b>X_</b> - Specify Beam <sup>1</sup>	<b>NN</b> - Not Needed <b>35</b> - 350 lm/ft <b>50</b> - 500 lm/ft <b>75</b> - 750 lm/ft <b>100</b> - 1,000 lm/ft <b>X_</b> - Specify lm/ft	<b>1CH</b> - 1 Circuit (Standard) <b>2CH</b> - Bi-Directional 2 Circuit (Optional, Independant Direct and Indirect Control)		
3) POWER & CONTROLS		4) FIXTURE MOUNTING & CONNECTIONS		
LINE VOLTAGE (DC)	REMOTE DRIVER (POWER) <sup>2</sup>	MOUNTING TYPE	CONNECTOR	
<b>UNV</b> - 120/277V <b>347</b> - 347V	<b>FDND</b> - Factory Non-Dimming <b>FD00</b> - Factory 0-10V 0.1% Dim <b>FD01</b> - Factory 0-10V 1% Dim <b>FD10</b> - Factory 0-10V 10% Dim <b>FDDA</b> - Factory DALI 0.1% Dim <b>FDDX</b> - Factory DMX Dim <b>FDTR</b> - Factory TRIAC Dim <b>LD01</b> - Lutron Hi-Lume 1% Dim <b>X_</b> - Specify Driver	<b>DWM</b> - Direct Wall Mount <b>MWM</b> - Mud-In Wall Mount	<b>SW</b> - Strip Wire	



EXAMPLE CODE: MFL375-W-4-PMW-90-35-OFL-DA7025-35-NN-NN-1CH-UNV-FD01-DWM-SW

Footnotes: <sup>1</sup> Contact factory about custom beam options. <sup>2</sup> Standard driver box is included.

OPTIONAL	
EMERGENCY BACKUP	WIRELESS MODULE
<p><b>EMC</b> - Emergency Circuit  <b>EMB</b> - Emergency Battery (10 W — Remote)  <b>X_</b> - Specify Backup</p> <p>Specify requirements at time of order.</p>	<p><b>WCN</b> - Wireless Communication Node (Connected to LED Driver In-Fixture or In-Driver Box)  <b>PIR</b> - Wireless Communication Node + PIR Sensor (Standard Lens for Low Bay &lt; 10')  <b>MW</b> - Wireless Communication Node + MW Sensor (Standard for Low Bay &lt; 10')  <b>X_</b> - Other – Specify Embedded Component or Specific Non-Standard Sensor Detection Range</p>

## DIMENSIONS & INSTALLATION

### Dimensions



### Standard Fixtures

2ft	23.05" / 23.4"
4ft	47.05" / 47.4"
6ft	71.05" / 71.4"
8ft	95.05" / 95.4"

Lens Length / Fixture Length

### Mounting Options

#### Wall Mount


Installs onto a wall. Available with a range of accessories, mounts and inserts that provide easy customization of visual appearance and performance enhancements.

#### Mounting Kit

##### Wall Mounting Kit

2.8" Stainless Steel Wall Mounting Plate, White and Black

#### Mounting Option



## SMARTBEAM® TECHNOLOGY

### The Ultimate Control of Lighting Distributions

SmartBeam makes it easy to specify the exact light required for any architectural space. Available in every XICO product; it is now possible to create truly tailored and engaging lighting that transform spaces, improves visual comfort, and saves energy.

To learn more about our SmartBeam Technology, please click or scan the QR Code.



### Direct Optics Choices

DIRECT OPTICS	BEAM PATTERN			
	DLAM	DBW60	DM50	DA5525
Flush Lens	■	■	■	■

### LPW Efficacy Conversion Chart

CODE	CCT SELECTED							
	2200K	2700K	3000K	3500K	4000K	5000K	5700K	6500K
80	–	0.91	0.96	1.00	1.04	1.11	1.11	1.11
90	–	0.91	0.96	1.00	1.04	1.11	1.11	1.11
95	–	0.91	0.96	1.00	1.04	1.11	1.03	1.04
SUN	–	0.90	0.92	1.00	1.01	1.07	1.04	1.05

### LPW Performance

	DIRECT			
	DLAM	DBW60	DM50	DA5525
LM/W	130	149	149	149

	INDIRECT		
	ILAM	IBW60	IA4560
LM/FT	130	149	149


$$LM/W = \frac{\left( \begin{array}{c} \text{DIRECT} \\ \text{LM/FT} \end{array} + \begin{array}{c} \text{INDIRECT} \\ \text{LM/FT} \end{array} \right)}{\left( \begin{array}{c} \text{DIRECT} \\ \text{W/FT} \end{array} + \begin{array}{c} \text{INDIRECT} \\ \text{W/FT} \end{array} \right)}$$

## DIRECT PHOTOMETRICS

48" Length, 80+/3500K CRI/CCT, 3,000 Lumens


Static White Light

**DLAM:** Lambertian




LM/FT	W/FT	LM/W
350	2.7	129.6
500	3.9	128.2
750	5.8	130
1000	7.7	129.9

**DBW60:** Batwing 60°




LM/FT	W/FT	LM/W
350	2.4	145.8
500	3.4	147.1
750	5.1	149
1000	6.8	147.1

**DM50:** Medium 50°



LM/FT	W/FT	LM/W
350	2.4	145.8
500	3.4	147.1
750	5.1	149
1000	6.8	147.1

**DA5525:** Asymmetric 55° at 25° Tilt




LM/FT	W/FT	LM/W
350	2.4	145.8
500	3.4	147.1
750	5.1	149
1000	6.8	147.1

## INDIRECT PHOTOMETRICS


48" Length, 80+/3500K CRI/CCT, 4,000 Lumens

**ILAM:** Lambertian




LM/FT	W/FT	LM/W
350	2.7	129.6
500	3.9	128.2
750	5.8	130
1000	7.7	129.9

**IBW60:** Batwing 60°



LM/FT	W/FT	LM/W
350	2.4	145.8
500	3.4	147.1
750	5.1	149
1000	6.8	147.1


**A4560:** Asymmetric 45° at 60° Tilt




LM/FT	W/FT	LM/W
350	2.4	145.8
500	3.4	147.1
750	5.1	149
1000	6.8	147.1

LED OPTIONS


80: Standard 80+ CRI




90: Standard 90+ CRI



95: High-Definition 95+CRI



SUN: Full Spectrum "SunLike"



CODE	DESCRIPTION	TYPICAL LED DATA							
		CCT	CRI	CRI R9	TM30 Rf	TM30 Rg	CQS	M/P Ratio	LPW
80	Standard 80 CRI	3500K	82.5	7.8	84	96.7	82.5	0.51	190
90	Standard 90 CRI	3500K	91	54.3	89.3	98.9	89.2	0.55	175
95	High Definition 95 CRI	3500K	97.1	95	-	-	-	0.70	163
SUN	Full Spectrum SunLike®	3500K	95	85	-	-	-	-	130

## POWER & CONTROLS

### Voltage

#### Fixture Voltage (AC)

120–277 VAC  
347 VAC, 50/60 Hz

#### Power Location

Remote

#### LED Driver

Factory Selected, 36–39V Constant Current

### Drivers

**FDND** - Factory Non-Dimming  
**FD00** - Factory 0-10V 0.1% Dim  
**FD01** - Factory 0-10V 1% Dim  
**FD10** - Factory 0-10V 10% Dim  
**FDDA** - Factory DALI 0.1% Dim  
**FDDX** - Factory DMX Dim  
**FDTR** - Factory TRIAC Dim  
**LD01** - Lutron Hi-Lume 1% Dim  
**X\_** - Specify Driver

### Emergency Backup (Optional)

**EMC** - Emergency Circuit  
**EMB** - Emergency Battery  
(10 W — Remote)  
**X\_** - Specify Backup

#### Power

10 W

#### Illumination Time

90 minutes

#### IP Rating

Suitable for Dry and Damp Locations,  
indoor use only

### XBox

#### Remote Driver Boxes (Optional)

To create a clean and organized power solution for multiple fixture installations see our Xbox Specification Guide. Reach out to a XICO Sales Representative to discuss your projects needs.

### Compatible Control Options



## TECHNICAL SPECIFICATIONS

### Finishes & Design Options

#### Housing Colors (Matte Finish)

White (RAL9003)  
 Black (RAL9005)  
 Gray (RAL7001)  
 Custom RAL



#### Housing Material

6063-T5 extruded, recycled aluminum

#### Mounting Brackets

Sheet Metal

#### Flat End Cap Material

Machined or cast aluminum

#### Lens Options and Material

Patented SmartOptics® made from Acrylic (PMMA)

### Standards & Certifications

#### Sustainability

Low carbon, environmentally conscious packaging and shipping methods

#### Compliance

BABAA & TAA compliant in-house manufacturing in Boston, MA with North American supply chain



#### Certifications



#### Declare Listed and Red List Free

Low carbon, environmentally conscious packaging and shipping methods

#### Recyclable

SmartOptics and all powder coated and anodized parts are fully recyclable at end of life

#### Manufacturing

All XICO products and associated optics and LED engines are assembled at our factory in Woburn, MA

#### Quality Assurance

Each product is engineered reliability and quality assurance tested

### Declare.

**Nano Series**  
 XICO Lighting  
 First Assembly: Woburn, MA, USA  
 Life Expectancy: 10+ Years  
 End of Life Option: Recyclable (99%)

**Ingredients:**  
 Aluminum, Glass, Oxide, Chemicals, Polymethyl methacrylate, Phenol, 4,4'-O-methylthiobis(2,6-dimethylphenol), 2,2'-bis[4-(4-hydroxyphenyl)phenyl]propane, 1,3-bis(phenoxymethyl)propane, 1,3-bis(phenoxymethyl)butane, 1,3-bis(phenoxymethyl)pentane, 1,3-bis(phenoxymethyl)hexane, 1,3-bis(phenoxymethyl)heptane, 1,3-bis(phenoxymethyl)octane, 1,3-bis(phenoxymethyl)nonane, 1,3-bis(phenoxymethyl)decane, 1,3-bis(phenoxymethyl)undecane, 1,3-bis(phenoxymethyl)dodecane, Polyethylene Glycol, Polyethylene Terephthalate, Barium Sulfate, Hexamethylenediamine, Phosphoric acid, Diphenyl ether, Iron, Silicones and Siloxanes, 4-Me. Chromium, metallic, Gold, Neodymium, Titanium, Zinc, Nickel, Phthalic

### Declare Listed

At Xico Lighting, we are committed to transparency and sustainability. That's why all our products are Declare listed, providing clear insights into their environmental footprint and safety. Look for these internationally recognized labels on Xico products, packaging, or at [xicoled.com/declare](http://xicoled.com/declare).



### Red List Free

Xico Lighting is dedicated to creating safe, sustainable solutions. All our products are Red List Free, meeting the highest industry standards for healthy and environmentally responsible materials as defined by the International Living Future Institute (ILFI). Learn more at [xicoled.com/declare](http://xicoled.com/declare).

### Quick Links

#### 5-YR Warranty



#### Business Terms



#### Patents & Trademarks



#### SmartBeam



#### Revit Files

